

FPC-12721-HD - QUICK PLUG

HARDWARE FEATURES

Enclosure:

- IP54 weatherproof rating
- Polycarbonate
- Includes mounting brackets Protection:
- Low voltage control and input circuitry
- No hard wiring needed

Control & interface:

- Electronic keypad
- Indicator lights for rain/mains water
- System test button for checking pump and valve function Inputs:
- Quick plug 12Vdc input for low level float switch
 Outputs:

CONTROLLER

- GPO for power supply to pump (240Vac 6Amp max)
- Quick plug 12Vdc output for solenoid valve
- Included with panel:
- 25mm female/female 12Vdc pulse latching solenoid valve (other sizes available)
- 9006 float switch with 10m cable & quick plug connector

SYSTEM TEST

FPC-SERIES

DANGER

• 10 Amp 3 pin 1.5m power supply lead

FUNCTION FEATURES

Operation:


- If rain water becomes available, the controller pulse closes
 the mains water valve and the pump will run
- In the event of rain water depletion or power failure, the controller pulses the valve open for mains water use





Quick plug float switch

Pulse latching solenoid valve



Base view



L

Code	Amp Rating	Enclosure Size
FPC-12721-HD	6 Amp Max	200x160x95mm

P: 1800 281 282 | F: 1300 281 282 | E: info@matelecaustralia.com.au | W: www.matelecaustralia.com.au Specifications are subject to change without notice | Images are a guide only and may differ from actual product