MULTI LEVEL FLOAT TREES - 4 FLOAT



The Multi Float Tree is a unique combination of floats, configured in a way that minimises installation/setup time and overcomes the many issues associated with float switch installations.

FEATURES

- Resin folled/potted connection Fully submersible
- Horizontal pivot point for switching accuracy and consistency
- Weighted Obviating flow induced travel No more tangled floats
- No more setting up with conduits and ties
- No more trying to pull multiple float wires through undersized conduit
- No more trying to decipher which wires relate to which floats

SPECIFICATIONS

Liquid temperature: Min 0°C (32°F), max 60°C (140°F)

Protection: IP68

Maximum depth: 9m (30ft)

Contact type: Mechanically activated, snap action N/O contacts

(close on rise) 250Vac 50/60Hz

210mm

260mm

260mm

260mm

226mm

CABLE WEIGHT

Max voltage: 250Vac 50/60Hz
 Max run current: 6 Amps (resistive)

Cable material: Floats - Neoprene rubber, Multicore - Polyvinyl chloride

Multicore cable size: Ø8mm / 5 x .75mm²
Housing material: Polypropylene

DIMENSIONS


HIGH

START

STOP

CONNECTIONS

These terminals are specific to MATelec Standard Single & Dual Pump Controllers



4 FLOAT TREE RANGE

Code	Description	Cable Length	Packing	MOQ	Ctn
FSW-12548	Multi Level Float Tree - 4 Float	20m	1	1	5