

# CORRUGATED CONDUIT



## NAIL IN

### FEATURES & BENEFITS

- Highly flexible | Heavy duty PVC
- Metre marked - easy measure
- High impact strength | Crush resistant
- Flame retardant | Self-extinguishing
- Extreme UV Resistant.

### PACKED DETAILS

Size: 47 x 47 x 24cm  
Weight: 8kg  
QTY/pallet 25

### SPECIFICATIONS

**Size / length:** 25mm x 50m  
**Material:** U-PVC  
Self-extinguishing  
Flame retardant  
**Ingress protection (IP):** IP66  
**Resistance to compression:** Min 1250Nt / 5cm  
**Complies to:** AS/NZS 2053.5:2001  
AS/NZS 5033:2012  
**Colour:** Grey and black  
**Minimum inside diameter:** 18mm  
**Outside diameter:** 24.8 - 25mm  
**Temp. range:** -5°C to +60°C



### CORRUGATED CONDUIT

Code	Description	Packing	MOQ	Ctn
CC-M25/50M-PV	Corrugated Conduit Solar HD - Grey 25mm x 50m	1	1	35/pallet
CC-M25/50M-PV-B	Corrugated Conduit Solar HD - Black 25mm x 50m	1	1	35/pallet